



مشخصات کلی و ابعاد دقیق فلومتر



YUYAO KINGTAI INSTRUMENT CO.,LTD

LZM Series Acrylic Flow Meter

LZM-ZT Series



Technical Parameters of LZM-ZT Series Flow Meter

Model	Range			Screw Thread	Accuracy	Size (mm)								
	GPM (Liquid)	LPM (Liquid)	Nm ³ /h(Gas)			A	B	C	D	E	F	G	H	
LZM-15ZAT		15-150LPH	0.1-1 0.16-1.6 0.3-3 0.4-4			157	32	150	35	25	60	25	110	
LZM-15ZT		10-100LPH	0.04-0.4 0.16-1.6 0.1-1 0.25-2.5 0.3-3 0.4-4 0.6-6 0.8-8 1-10 1.6-16 2.5-25 4-40	(M)1/2"BSPT (F)1/4"BSPT	±4%									
		16-160LPH												
	0.1-1	0.5-4				175	32	168	35	25	76	25	127	
	0.2-2	1-7												
	0.3-3	1-11												
	0.5-5	2-18												
LZM-25ZT	2-10	5-35	20-100 35-350 40-160 50-250	(M)1"BSPT										
	4-14	10-50												
	6-20	20-70				234	45	226	46	33	100	37	160	
	10-35	30-130												
	10-40	30-150												
	15-45	50-170												

جنس اجزای تشکیل دهنده ی فلومتر

The material of the LZM-ZT Series Flow Meter

Fitting	Float	O-ring
1.ABS 2.PP √3.PVC 4.Brass 5.Brass chromeplate 6.SS	√ 1.SS	√ 1.Silicon rubber 2.Fluorin rubber

Note:Mark with √, the material of the Flow Meter is the General Configuration