

## مشخصات کلی و ابعاد دقیق فلومتر


**FISCHER**  
UNDER LICENSE GERMANY

### LZM Series Acrylic Flow Meter

LZM serial flow meter, which is made of Acrylic, is used to measure the single-phase non-pulsating flux of liquid or gas. It is featured in beautiful look, low weight and durability.

#### LZM-6T<sub>2</sub>

■ LZM-6T O<sub>2</sub> Oxygen Flowmeter for concentrator. This Flow Meters is mainly used for measuring and controlling the flow of oxygen in oxygen concentrator



>>>



### Technical Parameters Of LZM-6T O<sub>2</sub> Series Flow Meter

Model	No.	Range (L/min)	Connection Type	Accuracy	Size ( mm )							
					A	B	C	D	E	F	G	H
LZM-6T O <sub>2</sub>	1	1-3	Tube	±5%	60	20	21or19	40	M10X1 or 9/16-18	8	22	8
	2	1-5			70	20		50		7	22	7
	3	0-5 0-9 0-10			93	20		70		10	22	8
	4	1-5 0-6			96	20		70		13	22	8
	5	0-5 1-5 0.1-1 2-10 0.5-10 0.5-14 4-25 0-1000cc/min			106	20		80		13	22	8
	6	1-5 0.5-10 2-10			108	20		70		25	22	8
	7	0-5 1-5 2-10 0.5-14			115.5	20		90		13	22	8

### The material of LZM-6T O<sub>2</sub> Series Flow Meter جنس اجزای تشکیل دهنده ی فلومتر

With valve	Valve	Fitting	Float	O-ring
T-With	✓ 1.Brass	✓ 1.Brass	✓ 1.Agate ball	✓ 1.Fluorinrubber
O-No	2.SS	2.Brass chromeplate	2.SS ball	2.Butyl